



## Technical Data Sheet

### PVC stabilizer for profile

Code: CPRS-603

#### Description:

Mixed metal complex stabilizer for extrusion of pipes is a complex extrusion compound suitable where long period of heat and light stability is required. It has excellent internal & external lubrication and can be applied for high speed extrusion and high temperature production. It imparts good light stability and high gloss to the finished product. Impact modifier may be added, if necessary.

#### Specification:

Appearance:	Powder/Flake
Color:	White
lead content:	50-55 %
Bulk density:	1.42 ±0.2 g/cm <sup>3</sup>
Moisture:	1% Max.

#### Area of Application:

CPRS-603 is an excellent cost performance stabilizer for production of outdoor windows and door profiles.

#### Recommended Mix:

Depending on the formulation, processing condition and the type of products, it varies in the range of 4.5-5 phr.

#### Packing Details:

Lined with a 25kg Polypropylene bag

www.caspian-polymer.com

E-mail : info@caspian-polymer.com | Hafez St, Dekhoda Blvd, Caspian Industrial Town, Qazvin-IRAN  
Sales : marketing@caspian-polymer.com | Tel : (+98) 283 284 81 50 - 2 Fax : (+98) 283 284 81 53  
Management : Management@caspian-polymer.com